

Marfak Na XD 00

Proven performance sodium soap grease
(formerly Marfak 00)



Product description

Marfak Na XD 00 is a proven performance fibrous sodium thickened grease designed to lubricate track rollers of crawler tractors, steering gears, and final drives of tractors, and industrial gearboxes, helping to provide a tough durable film, good adhesion and cohesion.

Marfak Na XD 00 is based on a sodium thickener, designed to help provide inherent rust protection by emulsifying small amounts of water, with good sealing properties.

Customer benefits

- Good film strength contributes to effective wear protection.
- Offers resistance against rust and dirt ingress.
- Formulated to emulsify small amounts of water.
- Designed to help provide inherent rust protection.



Marfak Na XD 00

Proven performance sodium soap grease
(formerly Marfak 00)

Applications

- Chevron recommends Marfak Na XD 00 for use in track rollers of crawler tractors, steering gears, and final drives of tractors where leakage with the normally recommended oil is excessive. It can also be used in industrial gear boxes designed for grease lubrication.
- Chevron recommends Marfak Na XD 00 for chassis lubrication for certain types of passenger cars, trucks, buses, farm, and construction systems when such type of Sodium Grease is recommended. It is also recommended for centralized lubrication systems

Approvals, performance and recommendations

Developed independently by Chevron to comply with the following performance standards and specifications:

MARFAK NA XD 00	
DIN 51 502: G00H-20	Meets the requirements
ISO 6743-9: ISO-L-XB(F)BAA00	Meets the requirements

Consult OEM representatives for independent verification, updates and recommendations.

Marfak Na XD 00

Proven performance sodium soap grease
(formerly Marfak 00)



Typical Test Data

MARFAK NA XD 00	TEST METHOD	RESULTS
Product Code		510890
ISO Viscosity Grade Base Oil Equivalent		1000
BOBV Kinematic Viscosity, mm ² /s @ 40°C	Calculated	1100
mm ² /s @ 100°C	Calculated	>45.5
Color	Observation	Dark Green
Thickener Type	CMM 164	Sodium
NLGI Grade		00
Worked Penetration, 60 mm/10	ASTM D217	400-430
Dropping Point, °C	ASTM D566	NA
Emcor Corrosion Test, Distilled Water	IP 220	0/0

ENVIRONMENT, HEALTH, and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions, and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the Product Information Center.

This Product Data Sheet (PDS) was produced for the Asia-Pacific region in good faith from the best information available at the time of issue. The specific information included may not directly reflect the local market or conditions. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. For the most up-to-date, country-specific information, please contact your local customer service center.

This document includes registered and unregistered trademarks, service marks, logos and trade names owned by Chevron Intellectual Property LLC and/or its affiliates, or owned by third parties whose products, services or standards are referred to. You must not use any trademark that appears in this document without permission from the relevant owner.

[Visit Product Information Center >](#)

Marfak Na XD 00/AP/CHV/PDSv1_280425



A Chevron company product

© 2025 Chevron Products Company. Asia Pacific.
All Rights Reserved.