

# Ultra-Duty® Grease

Specialty Industrial Grease



## Product description

**Ultra-Duty® Grease** is a premium, heavy-duty EP grease containing a high viscosity mineral oil, lithium thickener, effective EP additive, rust and oxidation inhibitors and tackiness agent.

## Customer benefits and product features

### Customer benefits

- **Protects metal surfaces**  
Outstanding film strength and effective EP additive protect against component wear under severe conditions and shock loading. Extreme tackiness maintains sealing collar of grease around bushings which prevents the ingress of abrasive dirt. Excellent resistance to water wash out ensures lubrication is maintained under extremely wet and muddy conditions.
- **Superior adhesiveness**  
Superior adhesiveness ensures grease stays in place and resists leakage, even in the most severe and shock load conditions, making it possible to extend relubrication intervals.
- **Protects against corrosion**  
Highly effective rust and corrosion inhibitors protect metal surfaces, even under extremely wet conditions.

### Product features

- Ultra-Duty Grease has stay-in-place properties that make it particularly suitable for industrial equipment operating in wet, muddy or dusty conditions.  
Red in color.

# Ultra-Duty<sup>®</sup> Grease

Specialty Industrial Grease



## Applications

Can include:

- Pulp and paper machinery
- Mining
- Logging and forestry
- Quarrying
- Material handling equipment
- Dredging equipment
- Offshore oil drilling
- Marine deck equipment
- General industrial greasing

In centralized lubrication systems where pumpability is a primary requirement, it may be necessary to use the NLGI 1 grade (depending on the design of the system).

Usable temperature range in continuous service is:

- NLGI 1: -20 to 140°C
- NLGI 2: -10 to 140°C

Maximum temperature for short term exposure is 155°C for NLGI 1 grade and 165°C for NLGI 2.

## Service considerations

Because of the heavy base oil viscosity and outstanding adhesive properties of Ultra-Duty Grease, it is recommended that a heavy follower plate be used in air-driven grease pumps. Depending on pipe sizing and distance, pumping rates will be lower than for conventional greases of the same NLGI grade. It may be necessary to use Ultra-Duty Grease 1 where pumpability is a primary requirement.

# Ultra-Duty® Grease

Specialty Industrial Grease



## Typical test data

ULTRA-DUTY® GREASE	RESULTS	
<b>NLGI Grade</b>	<b>1</b>	<b>2</b>
<b>Product Code</b>	<b>540951</b>	<b>540952</b>
Dropping Point, °C	174	180
Oil Viscosity,		
mm <sup>2</sup> /s @ 40°C	334	380
mm <sup>2</sup> /s @ 100°C	21.0	29.1
Penetration, Worked @ 25°C	325	280
Thickener (Lithium), m %	6	9
Timken OK Load, kg	32	32

1105

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by Chevron Global Lubricants: Asia Pacific.

ENVIRONMENT, HEALTH and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the [Product Information Center](#).

This Product Data Sheet (PDS) was produced for the Asia Pacific region based on the best available information at the time of issue. The specific information included may not directly reflect the market or conditions, and may vary. For the most up-to-date, country-specific information, please contact your local customer service center.

[Visit Product Information Center >](#)

Ultra-Duty® Grease /Asia Pacific/CHV/PDSv1\_04/2024



**A Chevron company product**

© 2024 Chevron Products Company. Asia Pacific.  
All Rights Reserved.